deDoelen

Grote Zaal

General Data:	3
De Doelen Address:	3
Technical Information and Inquiries:	3
The building:	4
Backstage, Dressing Rooms and Soloist Room:	4
Green Room:	4
Smoking and Smoke/Fog Effects:	4
Internet/Wifi:	4
Electrical Power:	4
Loading Zone/Platform:	4
Elevators:	4
Mobile Elevating Platforms:	4
Grote Zaal	5
General:	5
Lighting:	6
Sound:	7
Electrical Power:	8
AV:	8

General Data:

De Doelen Address:

Public Entrance / Ticket Booth : Schouwburgplein 50

Supply-/ Artists Entrance : Kruisstraat 2
Postal Code : 3012 CT
City : Rotterdam
General Telephone Number : 010-2171700

Technical Information and Inquiries:

Planners Technical & Av: Nicky van Spronsen, Devin de Groot and Tommy Evers rooster.td@dedoelen.nl


In the absence of the planner Technical & Av, you can contact the head of the department; Remko van Es: r.vanes@dedoelen.nl

Accessibility:

The artist's entrance is located at Kruisstraat 2.

Due to limited parking space, it is necessary to reserve parking spots in advance for the load in/out.

For long-term parking there are several other parking options nearby.



The building:

The building consists of three (3) quarters. Respectively called the Willem Burger Quarter, The Jurriaanse Quarter and the Grote Zaal Quarter.

Backstage, Dressing Rooms and Soloist Room:

All rooms can be locked and are provided with security keycards Lockers are present in all rooms.

Monitor capabilities are present in all rooms.

Green Room:

Breakfast, lunch and dinner are available but require inquiry in advance.

Smoking and Smoke/Fog Effects:

De Doelen is a smoke-free environment.

The use of smoke machines during performances is possible on request. Due to the mandatory presence of a fire watch additional costs are involved.

Internet/Wifi:

In the whole Doelen complex there is free Wi-Fi available, accessible through SSID 'de Doelen'. There are options on request, for a fee, to have a dedicated Wi-Fi Access point for each event.

Electrical Power:

There are several high voltage power connections available throughout the facility.

Loading Zone/Platform:

The loading zone is located at Kruisstraat 2 or Kruisstraat 4. If you need to use one of the loading zones, please indicate this in advance.

Elevators:								Floors						
	Height	Width	Depth	Door Width	Door Height	Weight	Persons	В	GF	1	2	3	4	5
Reception														
Elevator	2,1	1,8	2,8	1,8	2,1	2000kg	n/a	X	х	x	X			
Royal														
Elevator	2,2	1,5	1,19	0,97	2,08	1000kg	13		Х	X	х	х		
Expedition														
Elevator KS4	2,15	2,8	3	1,98	2,05	5275kg	16	X	Х					
Double														
Elevator BIG	2,2	1,68	3	1,68	2,09	2900kg	38	X	Х	X		х	X	
Double														
Elevator														
SMALL	2,1	1	2,15	0,89	2,09	1250kg	16		х	X		Х	Х	
Service														
Elevator WBH	2,1	1,2	2,6	1,28	2,08	1250kg	16	х	х	X	Х	Х	х	х
Elevator EFZ	2	1,4	1,12	1,03	1,98	1000kg	13		Х	х	х			

Sizes in Meters.

Mobile Elevating Platforms:

There are 3 mobile elevating platforms to use. These don't go on stage of the Grote zaal.

Grote Zaal

General:

Elevators:	Reception (goods) Royal Elevator (persons) EFZ Elevator (persons)				
Stage: FOH:	1 st Floor 2 nd Floor				
Smoke Alarm:	Yes (deactivation available on request)				
Seating:	Max: 2252				
Control location:	In the Grote Zaal or one of the control rooms at the ba				
Smallest dimension to stage:	Height Width	1.99 mtr. 1.16 mtr.			
Stage Dimensions:	See floorplan (available on request)				
Elevator for Piano: Dimensions: Stage Floor:	Width Length Capacity	stage (see floorplan) 2.00 mtr. 3.50 mtr. 1.500 Kg nade up of 32 movable lifting tables, which			
	can rise to the rear of the stage (like an amphitheater) from 40 to 150 cm. With this, an ideal stage structure can be realized for every event. The stage is computer-controlled, which means that quick changeovers can be realized. The stage sections are provided below the surface with cable ducts, connections for audio, lighting, video, data, 230v power and 24v power for music stand lighting.				
Ballet Floor:	Available (Black)				
Curtain:	Black backdrop (upon request)				
Maximum LX height: (technical ceiling)	10,6 meters. (For amplified concerts a height of 10,3 meter is recommended) Minimum height of the ceiling is 10 meters due to the PA				
Technical crew:	The technical crew has the right to take a lunch and/or diner breaks during their respective moments of the day. The maximum amount of hours a technician is allowed to work is 12 hours. If the length of the event is larger than				

that (including build up and break down), extra workshifts will be scheduled.

Lighting:

Location cabin: At the back corner of the Grote Zaal.

Possibility to open a window: Yes

Light console: MA Lighting GrandMA 3 light (MA2 & MA3 showfiles

available)

Hall lighting on DMX: Yes

Music stand lighting: DMX controllable led lights

Control-protocol: The installation is controllable via sACN. Control via

analog DMX is possible in consultation but is not

preferred.

Patch list and light plot: On request

Individual Dimmer Channels: 24 dimmers on stage and 56 in LX's.

Light fixtures fixed install: 24x Robe - Robin Iparfect 150 FW RGBA (Backlight)

8x Robe Robin T1 Profile (Backlight)

12x JB - Lighting P12 Profile Spot Led (Backlight and top)

4x Blinders

58x ETC D60 Lustr+ (Concert Lights)

22 ADB 2kW PC (front boxes)

2 Niethammer 2kW Profile (front boxes) 12 ADB Warp motorized 800W (front boxes) 44 Niethammer 2kW Profile (front bridges)

12 JB - Lighting P12 Profile Spot HCRI (front bridges)

3 ADB Warp motorized 800W (left) 4 Niethammer 2kW Profile (left) 3 ADB Warp motorized 800W (right) 4 Niethammer 2kW Profile (right)

2 Followspot Robert Juliat Aramis HMI 2500W

RGB Hall lights and RGB Led Strips in the sides of the hall

Sound:

P.A.:

Main system: Line array left and right, each side 8 cabinets D&B V80

with array processing.

Fill-ins back ring: 2x D&B Y10P 110x40

Fill-ins side ring: 1x D&B Y10P 110x40 per side

Fill-ins stage edge: 10x D&B 5S

Fill-ins ground floor: 1x D&B V7P per side

Subwoofer: 2x D&B V-GSUB on stage per side (add-on, not

necessary)

Sub- Array 8x V-Sub above technical ceiling

Loges: 3x D&B 4S per side Processing: D&B R1 + R90

Input: Analog or AES/EBU or Dante or Madi thru DAD AX32

Monitors: 8x D&B M6

Mixers: Allen & Heath Dlive S7000 with Allen & Heath Dlive CDM64

Mixrack.

Upon request: Dlive C3500 with CDM48 Mixrack. Analog Splitrack

available

Intercom: Greengo (Wired and Wireless)

The audio system is capable of producing high volumes. However, we adhere to the MUSIC SECTOR HEARING DAMAGE PREVENTION covenant which says to limit audio emissions to a highest equivalent average noise level of Leq=100 dB (A), measured over 15 minutes.

We expect everyone to adhere to these agreements. Due to the big reverberation in the room we would like to ask you to listen to expertise of our sound technicians gathered trough the years.

Electrical Power:

Stage right: 1x 125A

2x 63A 4x 32A

Stage left: 1x 63A

1x 32A (for Audio)

AV:

Projection screen: Electric Roller Screen.

Size 12m x 9m (W x H; maximum)

Roll up / down approx. 30 sec. 9 meter

Projector: Panasonic PT-RQ35K

30.500AL

SDI connection

Led Screens: 2 (placed left and right of the organ)

Resolution: 1024x640 Dimensions: 4.00x2.50m p3.9

Resolution per tile: 128x256 Tile dimension: 500x1000 2.700 nit

max 270W/m2

Scaler: Barco DSC200

inputs: 1x HD-SDI, 2x DVI-D input scaling: 1920x1080p60

output scaling: 1024x640 -> 2x black bar at a 16:9 input.

Video Mixer: BlackMagic Production Studio 2M/E Controller: BlackMagic Advanced Panel 1M/E

Note: The system runs at 1080p50

Camera's, recorders, streaming devices and other peripherals available various SDI and Fiber patch points backstage, on stage and FoH.